

BIG PICTURE

ROE
CREATIVE DISPLAY

MC-12H Specifications

**12MM Mesh - Indoor / Outdoor
in ACASS-SYSTEMS TOURING FRAMES**

FEATURES

Good flexibility - mix and match hollow to satisfy your design.

Transparency (21%) and refresh rate (4000Hz)

Tour frame - fast installation, saving more time and cost

Waterproof - no risk of damage due to weather or humidity

SPECIFICATIONS

Pixel Pitch	12.5mm	Viewing Angle	110°
Pixel Density	6400/sqm	Module Weight	6.5kg
Brightness	6000 Nits	Processing Depth	16 Bit
LED Type	SMD 3-in-1	Ingress Protection Rating	IP65
Tile Size (W x H x D)	600x600x85	Refresh rate	4000Hz
Transparency	21%	Max Power per Tile	320W
Pixels per Module	48 x 48	Temperature	-20 - 45°C
Pixel /m²	6,400		

Rental Module (ACASS-SYSTEMS)

2 x 1

Module Size	1200 x 600 mm
Resolution	96 x 48 pixels
Weight p/ Module	36kg

1 x 1

Module Size	600 x 600 mm
Resolution	48 x 48 pixels
Weight p/ Module	14kg

2 x 2

Module Size	1200 x 1200 mm
Resolution	96 x 96 pixels
Weight p/ Module	56kg

1 x 2

Module Size	600 x 1200 mm
Resolution	48 x 96 pixels
Weight p/ Module	36kg

Frames are housed in 6 way cart (163kgs)

LED displays